

Snorkel or Scissors Lift Daily Checklist

DATE: _____ **OPERATOR:** _____ **SHIFT:** _____

VISUAL CHECKS	PASS	FAIL	REMARKS
Tire and Wheel Condition			
Outriggers (if equipped)			
Railings, Entry Gates, Chains			
Loose Railing Pins/Hardware			
Leaks (hydraulics, brakes)			
Frayed Cables/Hoses			
Structural Damage/Welds			
Loose/Damaged Electrical Cords			
Loose/Damaged Connectors			
Loose/Damaged Controls			
Loose/Damaged Wiring			
Hour Meter			
Gauges and Instruments			
Battery Fluid Level			
Battery Connector			
Hydraulic Oil Level			
Decals/Warning Labels			
Operators Manual			
ANSI Manual of Responsibilities			

OPERATIONAL CHECKS	PASS	FAIL	REMARKS
Horn (if equipped)			
Steering			
Brakes			
Parking Brake			
Operating Controls			
Emergency Controls			
Pothole Protection			
Tilt Alarm			
Battery Charger			
Battery Discharge Indicator			
Attachments			
Safety Devices			
Operate/Check Jib			
Operate/Check Mast Chains			

CAUTION: ANY SNORKEL OR SCISSORS LIFT FOUND TO BE IN NEED OF REPAIR, IS UNSAFE, OR CONTRIBUTES TO UNSAFE CONDITIONS, MUST BE REMOVED FROM SERVICE AND A SUPERVISOR NOTIFIED. IF THE SNORKEL OR SCISSORS LIFT BECOMES UNSAFE WHILE IN OPERATION, REMOVE FROM SERVICE, TAGIT OUT OF SERVICE AND NOTIFY SUPERVISOR. ONLY AUTHORIZED PERSONNEL ARE ALLOWED TO REPAIR OR MAKE ADJUSTMENTS ON SNORKEL OR SCISSORS LIFTS.